

# Card reader with PIN


Hikvision card reader with PIN keypad DS-K1108AMK for TapHome. Two-factor authentication, Mifare, Wiegand, IP65.



## Quick Facts

Dimensions	50 × 158 × 17 mm
Operating temperature	-35 ... 60 °C
IP rating	IP65

Card reader with PIN keypad supporting Wiegand protocol.

Order Code	DS-K1108AMK
EAN	 6954273653729

## Technical Specifications

ELECTRICAL	
Power supply	12 VDC
Power consumption	3 W
INTERFACE	
Frequency	13.56 MHz (Mifare) / 125 kHz (EM)
Reading distance	EM ≤100 mm, MF ≤50 mm
Standard	ISO14443-A
Protocol	Wiegand 26/34

## Features

---

- For security purposes, entrance cards and key fobs can only be scanned after the reader has been closed and restarted after installation. It is not possible to scan cards or key fobs with an opened reader.
- Communication Mode: RS485/Wiegand (w26, w34) connected into TapHome Wiegand module
- Card Reading Distance: EM Card:  $\leq 100$  mm ( $\leq 3.94$ "") Mifare Card:  $\leq 50$  mm ( $\leq 1.97$ "")
- Frequency: 13.56MHz
- Frequency Standard: ISO 14443-A
- Processor: 32-bit
- Installation: Wall Mounting with/without Gang Box
- Protection Level: IP 65
- <https://taphome.com/docs/manuals/CardReaderDSK1108.pdf>



**Product page**

<https://hardware.taphome.com/hikvision-pin-reader/>

