

# Universal box

KOPOS installation boxes for TapHome modules.  
Variants for brick/concrete and drywall, depth 45mm or 70mm.



## Quick Facts

Dimensions	55 × 55 × 45 mm
Operating temperature	-10 ... 60 °C
IP rating	IP20

KOPOS device boxes for TapHome touch switch installation. Available in brick/concrete (flush mount) or drywall (hollow wall) variants.

## Product Variants

Order Code	Hĺbka	Druh montáže	EAN
KOPOS KP 68/D_KA	45mm	Tehla / betón	 8595568932327
KOPOS KPR 68/D_KA	70mm	Tehla / betón	 8595568932334
KOPOS KPRL 68-70/LD_NA	70mm	Sadrokartón	 8595568925879
KOPOS KUL 68-45/LD_NA	45mm	Sadrokartón	 8595568929709

## Technical Specifications

---

### GENERAL

Material	ABS
Compatibility	Flush-mount TapHome modules (2-UI, 4UI-2DO, 6-UI, etc.)

---

### Flush mount boxes (brick / concrete)

---

**KP 68/D** (depth 45mm) and **KPR 68/D** (depth 70mm) - Diameter: 73 mm - Milled hole diameter: 80 mm - Option for rigid connection in continuous row with 71 mm spacing - Entry holes made of flexible material - airtight even with cable inserted - Suitable for low-energy and passive houses - Protection rating: IP30 - Temperature resistance: -5 to +60 °C - Standard: ČSN EN 60 670-1

### Drywall boxes (hollow walls)

---

**KUL 68-45/LD** (depth 45mm) and **KPRL 68-70/LD** (depth 70mm) - Diameter: 73 mm - Milled hole diameter: 73 mm - Mounting and device screws with double thread for quick installation - Entry holes made of flexible material - airtight - Suitable for low-energy, passive houses and soundproof walls (attenuation up to 69 dB) - Protection rating: IP30 - Temperature resistance: -5 to +60 °C - Standard: ČSN EN 60 670-1



Product page

<https://hardware.taphome.com/universal-box/>

